

LogiLink®

Audio Converter

Digital COAX/Toslink to Analog

Art. No.: CA0100




Converts digital Coaxial or Toslink audio signals to analog L/R audio.



Features:

- » Converts Coaxial or Toslink digital audio signals to analog L/R audio
- » Supports sampling rate at 32, 44.1, 48 and 96 kHz
- » 24-bit S/PDIF incoming bit stream on left and right channels
- » Provides electromagnetic-noise-free transmission
- » Easy to install and simple to operate



Speaker

Specification:

Input Connector	1x Digital Coax Audio (RCA) female 1x Toslink (SPDIF; Optical) female
Output Connector	Stereo Audio (2x RCA) female
Specification	2 channel (stereo) supported
Sampling Rate	32/44.1/48 and 96 kHz
Operating Temperature	0–70 °C
Operating Humidity	10–85% RH (no condensation)



Made in China



RoHS
compliant



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

LogiLink®

Audio Converter

Digital COAX/Toslink to Analog

Art. No.: CA0100



Storage Temperature	-10–80 °C
Storage Humidity	5–90% RH (no condensation)
External Power Supply	5 V/1 A
Power Consumption	0.5 W max.
Dimensions	5.1x4.1x2.6 cm
Weight	78 g



Package Contents:

- » 1x Audio Converter
- » 1x Power Supply Set
- » 1x User Manual

Package Information:

- » Packing Dimension: 149x110x40 mm
- » Packing Weight: kg
- » Carton Dimension: mm
- » Carton Q'ty: pcs
- » Carton Weight: kg



Made in China



*The specifications and pictures are subject to change without prior notice.
*All trade names referenced are the registered trademarks of their respective owners.

Best Connectivity