

# LogiLink®



## Ultra Slim 4K Pro 1x4 HDMI™ Splitter with Mounting Bracket

Art. No.: CV0143

This 1x4 HDMI Ultra HD Splitter with HDCP 2.2 is an advanced solution for splitting a single HDMI input to four HDMI outputs.

It provides high performance audio and video output up to 4K2K@60Hz resolution and delivers up to 18Gbps of bandwidth, ensuring the best 4K picture quality.

Its ultra-sleek design with a thickness of 15mm and a length of 130mm fits in the palm of your hand, and can easily be discreetly hidden behind monitors or TVs.

### 1 Input to 4 Outputs

Connects one HDMI source to four HDMI displays.



### Built-in Mounting Bracket

Securely install on most surfaces.



5V/2A power adapter included



Made in China



RoHS  
compliant



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.

# LogiLink®



## Ultra Slim 4K Pro 1x4 HDMI™ Splitter with Mounting Bracket

Art. No.: CV0143

### Feature:

- » Compliant with HDMI 2.0b and HDCP™ 2.2 specifications
- » Supports video formats up to 4K@30Hz with 24-bit RGB/YCbCr 4:4:4/YCbCr 4:2:2, and up to 4K@60Hz with 12-bit YCbCr 4:4:4
- » Supports 3D frame sequential video formats up to 1080p@60Hz
- » Supports high resolution VESA® mode video formats up to QSXGA@60Hz
- » Supports LPCM 7.1-channel, Dolby TrueHD™, DTS-HD Master Audio™, and HDR (High Dynamic Range)
- » Supports Auto EDID analysis mode, equipped with EDID emulation
- » Full YCbCr 4:4:4 Chroma Sampling at 4K
- » LED indicators for power status and source devices
- » Plug-n-Play, no drivers required

### Specifications:

|                         |  |
|-------------------------|--|
| Input                   | HDMI, female x 1                           |
| Output                  | HDMI, female x 4                           |
| Output Resolution       | 480i~1080P@50/60, 4K2K@30, up to 4K2K@60Hz |
| Video Bandwidth         | 600MHz/18Gbps                              |
| Operating Temperature   | 0°C~45°C                                   |
| Operating Humidity      | 10%~85% RH (non-condensing)                |
| Storage Temperature     | -10°C~80°C                                 |
| Storage Humidity        | 5%~90% RH (non-condensing)                 |
| Power Supply            | DC 5V/2A                                   |
| Chassis Material        | Aluminum                                   |
| Power Consumption (Max) | 2.75W                                      |
| Product Dimension       | 130 x 75 x 15mm                            |
| Product Weight          | 240g                                       |

### Package Contents:

- » 1 x HDMI Splitter
- » 1 x 5V/2A Power Adapter
- » 1 x User Manual

### Package Information:

- » Packing Dimension: 176 x 140 x 40mm
- » Packing Weight: 0.4kg
- » Carton Dimension: 470 x 310 x 200mm
- » Carton Q'ty: 20pcs
- » Carton Weight: 8.6kg



Made in China



RoHS  
compliant



\*The specifications and pictures are subject to change without prior notice.  
\*All trade names referenced are the registered trademarks of their respective owners.