

LogiLink®

USB-C™ HiFi Sound Card 96kHz/24bit DAC with 3-Level EQ

Art. No.: **UA0363**

This mobile DAC adapter converts digital Audio signals to analog audio and connects to any headphones via 3.5mm headphone cable. Improves headphone audio dynamic effects with Hi-Fi sound performance; perfect for gamers, Youtubers, music players, etc.

USB-C

Thanks to its ultra-compact form, this USB-C DAC fits into any pocket and is perfect for use on the go.







Comfortable Extras at the Push of a Button

Compatible with popular headphone in-line controls and equipped with an interchangeable hardware equalizer; this allows you to adjust audio output to suit your listening preference with just one button.



A sampling rate of 96 kHz at 24 bits and an outstanding noise ratio of 100 decibels, this adapter delivers a breathtaking audio experience. Enjoy original and pure sound of your favorite music, videos or movies.











LogiLink_®

USB-C™ HiFi Sound Card 96kHz/24bit DAC with 3-Level EQ

Art. No.: **UA0363**

High Compatibility

Fully compatible with most smartphones and notebooks with USB-C connections, in the market.

An Affordable Solution for HiFi Sound

Provides the most economical solution to enjoy high quality sound performance instead of buying an expensive Bluetooth headset.

On Air Everywhere!

With the handy cable design, you're not only have a powerful headphone amplifier in your pocket, but it's also more comfortable to listen to music while working and walking.













LogiLink_®

USB-C™ HiFi Sound Card 96kHz/24bit DAC with 3-Level EQ

Art. No.: **UA0363**

Specification:

- » USB-C complies with USB2.0 specification
- » USB Bus-Powered mode, no external power required
- » DAC: BES Technic BES3100
- » Headphone Amplifier: Maxim MAX97220AA
- » Supports sampling rates of 44, 48, 96 kHz with a 24-bit resolution
- » Built-in microphone for supported mobile phones
- » 3 Built-in levels for the hardware equalizer (EQ), selectable by control button
- » Supports most 3.5mm 3 pole 16-600ohm headsets in the market
- » Output power (W): 125mW (max) per channel
- » Signal to Noise Ratio (SNR): around 100dB (A-weighting)
- » Total Harmonic Distortion (THD+N): 0.003% (A-weighting)
- » Crosstalk: >=110dB
- » LED indicator for sampling rate/EQ modes
- » Fully Plug & Play, and Hot Swap compatible
- » Supports most mobile phones with USB-C interfaces (Google Pixel 2 /2XL / Nexus, Motorola Z / Z2 / Huawei Mate9 / Mate10, Xiaomi, One Plus5 / 5T, LeEco, Smartisan, Nubia, Asus, Samsung S8 / S9 / Note8, LG V30, Sony & Nokia)
- » Supports notebooks with USB-C connectors (MacBook, MacBook Pro, HP, Dell, Samsung)

Package Contents:

- » 1x USB-C HiFi Sound Card 96kHz/24bit DAC with 3-Level EQ
- » 1x User Manual

Package Information:

- » Packing Dimension: 137x148x12 mm
- » Packing Weight: 0.015 kg
- » Carton Dimension: 465x300x360 mm
- » Carton Q'ty: 250 pcs» Carton Weight: 4.69 kg







*The specifications and pictures are subject to change without prior notice. *All trade names referenced are the registered trademarks of their respective owners.